

CHTDL Series Duct CO₂/Humidity/Temp

- LCD display with field calibration menu
- 2000/5000 ppm CO₂; 2% RH
- Integrated set-point relay
- Field replaceable NDIR CO₂ element



DESCRIPTION

Senva CO₂ sensors maximize energy savings by ensuring optimal ventilation. Measuring exhaled CO₂ levels ensures air is conditioned only when needed. This unit combines CO₂, humidity, and temperature sensing all in one compact device, reducing sensors required, installation labor and provides a cleaner IAQ solution.

APPLICATIONS

- Controlling ventilation in response to occupancy
- Facilitates compliance with ASHRAE 62.1 standard for air quality
- Offices, conference rooms, and public assembly areas

FEATURES

CO₂, humidity, and temperature all in one device...fewer units to buy and install

- LCD display for easy set up of all parameters
- Options for complete control including set-point
- 0-10V outputs standard. Thermistors optional

High performance NDIR CO₂ with set-point relay


- Non-dispersive infrared sensing element (NDIR)
- Selectable auto-calibration mode returns sensor to baseline values
- Field replaceable CO₂ sensor
- 2000 or 5000 ppm scale

2% RH sensor

- On-board temperature compensation for RH eliminates temp coefficient errors achieving excellent measurement accuracy, high repeatability and offset stability.

Quality

- Industry leading 7-year limited warranty/ 2-year RH element, 3-year CO₂ element limited warranties



Display and menu

- Easy set point and calibration adjustments. Set offsets for CO₂



Field replaceable element

- Display and menu
- Easy set point and calibration



ORDERING
CHTDL -

 CO₂/Temp/RH (2%)

Thermistor Addition*

Blank = None
 C = 100Pt (385)
 D = 1000Pt (385)
 E = 10k type 2
 F = 10k type 3
 G = 10k w/11k shunt
 H = 3k
 I = 2k2
 J = 1k8
 K = 20k'
 L = 100K

*Addition of Thermistor requires the removal of the setpoint relay on the circuit board of the CHTDL.

To order replacement sensor elements, please consult factory

SPECIFICATIONS

Power Supply	12-30VDC/24VAC ⁽¹⁾ , 100mA max.	
Outputs	CO ₂ , RH, and Temperature Transmitters 3 wire 0-5/0-10V ⁽²⁾ (jumper selectable)	
CO ₂	Type	Non-dispersive Infrared (NDIR)
	Accuracy	±40ppm ±3% of reading
	Response time	60 seconds to 90% reading
	Output update rate	3 seconds
	Output scaling	0-2000 ppm (default), 0-5000 ppm (option)
	Programmable set point	Solid-state output, 1A @ 30VAC/DC, N.O.
	Relative Humidity	Type
Accuracy		+/-2% over 10 to 90%RH range
Resolution		0.05%RH
Hysteresis		+/-1%RH
Non-Linearity		factory linearized <1%RH
Temperature coefficient		fully compensated on-board
Response time ⁽³⁾		30s
Output update rate		2s
Operating range		0 to 100%RH (non-condensing)
Long term drift		<0.5%RH per year
Temperature (transmitter specifications; thermistors optional)	Operating conditions ⁽⁴⁾	-20° C to 60° C @ RH>90% -20° C to 80° C @ RH=50%
	Scaling	32 to 122° F (0-50° C)
	Accuracy (-20 to 70° C range)	<+/-1° C; 0.5° C typ @ 25° C 3% models, <+/-2° C; 0.5° C typ @ 25° C
	Resolution	0.01° C
	Repeatability	+/-0.1° C
	Response time (3)	30s
	Output update rate	2s
LCD Menu Setup Parameters	Operating range	-40° C to 120° C (sensor only)
	SPH, Setpoint, Hi (On) point	500ppm to full-scale (700ppm default)
	SPL, Setpoint, Lo (Off) point	400ppm to full-scale-50 (600ppm default)
	SEL, Scaling	0-2000ppm or 0-5000ppm (2000ppm default)
	Adj, Adjustment	Offset adjustment +/-250ppm (0 default)
Operating Environment	CAL, Calibration mode	Automatic mode ON or OFF (default=ON)
	Run mode	Displays CO ₂ in ppm
	Temperature	32 to 122F (0 to 50C)
Enclosure	Humidity	0-95% non-condensing
	Material	ABS/Polycarbonate
	Dimensions	4.0' h x 4.4" w x 2.1" d (+6.8" probe)

(1) One side of transformer, secondary is connected to signal common. Dedicated transformer is recommended.

(2) 15-30 VDC/24VAC power supply voltage required for 10V output

(3) Time for reaching 63% of reading at 25° C and 1 m/s airflow

(4) Long term exposures to conditions outside normal range at high humidity may temporarily offset the RH reading (+3%RH after 60 hours.)